

DECLARATION OF PERFORMANCE CPR-112/2020 DP017EN20493001

1. Unique identification code of the product-type: **Acriflex Mono.**
2. Intended use/es: **Liquid applied water impermeable products for use beneath ceramic tiling bonded with adhesives.**
3. Manufacturer: **Diasen Srl - zona Ind.le Berbentina, 5 - 60041 Sassoferrato (AN) - www.diasen.com**
4. System/s of AVCP: **System 4;**
System 3 for water resistance.
5. Harmonised standards: **EN 14891:2012**
Notified body/ies: **The Notified Test Laboratory CertiMaC s.c.a r.l. n°: 2685, determined the type product on the basis of type tests on samples taken by the manufacturer, according to SYSTEM 3.**
6. Declared performance/s:

Essential characteristics	Performances
Initial tensile adhesion strength	≥ 0,5 N/mm ²
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²
Tensile adhesion after contact with lime water	≥ 0,5 N/mm ²
Waterproofing	No penetration or weight gain ≤ 20g
Crack bridging ability (under standard conditions).	NPD
Dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)**
Sassoferrato, 30/11/2020

DiaSen srl
Z. Ind.le Berbentina, 5
60041 Sassoferrato (AN)
P. IVA/C.F. 01553210426

 2685	 Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy www.diasen.com
<p style="text-align: center;">20 CPR-112/2020 EN 14891 ACRIFLEX MONO</p> <p style="text-align: center;"><i>Liquid applied water impermeable products for use beneath ceramic tiling bonded with adhesives.</i></p>	
<p>Initial tensile adhesion strength</p> <p>Tensile adhesion strength after water contact</p> <p>Tensile adhesion strength after heat ageing</p> <p>Tensile adhesion strength after freeze-thaw cycles</p> <p>Tensile adhesion after contact with lime water</p> <p>Waterproofing</p> <p>Crack bridging ability (under standard conditions).</p> <p>Dangerous substances</p>	<p>≥ 0,5 N/mm²</p> <p>≥ 0,5 N/mm²</p> <p>≥ 0,5 N/mm²</p> <p>≥ 0,5 N/mm²</p> <p>≥ 0,5 N/mm²</p> <p>No penetration or weight gain ≤ 20g</p> <p>NPD</p> <p>See SDS</p>

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
 Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com

PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
 Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

