# IASEN GREEN RUULDING EUTURE

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Acriflex Mono

# 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Waterproofing. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

### 1.3 Details of the supplier of the safety data sheet:

Diasen S.r.l.

Zona Ind.le Berbentina, 5

60041 Sassoferrato (AN) - Marche - Italia

Phone.: +39 0732 9718 - Fax: +39 0732 971899

diasen@diasen.com https://www.diasen.com

### 1.4 Emergency telephone number:

### **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

#### Warning



### **Hazard statements:**

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

### **Precautionary statements:**

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P314: Get medical advice/attention if you feel unwell

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

# **Supplementary information:**

EUH208: Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction

# Substances that contribute to the classification

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Non-applicable

# 3.2 Mixture:

Chemical description: Aqueous emulsion

**Components:** 

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:



# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification		Concentration
CAS:	64742-82-1	Hydrocarbons, C9-C1	12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)□¹□	Self-classified	
EC: Index: REACH:	919-446-0 Non-applicable : 01-2119458049-33- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT RE 1: H372; STOT SE 3: H336; EUH066 - Danger		1 - <2,5 %
CAS:	107-21-1 203-473-3 603-027-00-1 : 01-2119456816-28- XXXX	Ethanediol □ <sup>2</sup> □	☐ Self-classified		
EC: Index: REACH:		Regulation 1272/2008	Acute Tox. 4: H302; STOT RE 2: H373 - Warning	<b>(1)</b>	<1 %
CAS: EC:	55965-84-9 Non-applicable 613-167-00-5 : Non-applicable	reaction mass of 5-c 3-one (3:1) $\square$ <sup>1</sup> $\square$	hloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-	ATP ATP13	
Index: REACH:		Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger		<1 %

 $<sup>\</sup>square^{1}\square$  Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

# **SECTION 4: FIRST AID MEASURES**

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

# By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

# 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

<sup>□</sup>²□ Substance with a Union workplace exposure limit

# IASEV<sup>®</sup>

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

# 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

	Identification	Environmental limits			
Ethanediol		IOELV (8h)	20 ppm	52 mg/m <sup>3</sup>	
CAS: 107-21-1	EC: 203-473-3	IOELV (STEL)	40 ppm	104 mg/m <sup>3</sup>	

### **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	44 mg/kg	Non-applicable
EC: 919-446-0	Inhalation	Non-applicable	Non-applicable	330 mg/m <sup>3</sup>	Non-applicable
Ethanediol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-21-1	Dermal	Non-applicable	Non-applicable	106 mg/kg	Non-applicable
EC: 203-473-3	Inhalation	Non-applicable	Non-applicable	Non-applicable	35 mg/m <sup>3</sup>

### **DNEL (General population):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
EC: 919-446-0	Inhalation	Non-applicable	Non-applicable	71 mg/m³	Non-applicable
Ethanediol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 107-21-1	Dermal	Non-applicable	Non-applicable	53 mg/kg	Non-applicable
EC: 203-473-3	Inhalation	Non-applicable	Non-applicable	Non-applicable	7 mg/m³

### PNEC:

Non-applicable

### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

# B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

<sup>&</sup>quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

# **ANDIASEN**

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	CAT III	EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	CAT III	EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
<b>==</b> .	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>⊢</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 1,01 % weight

V.O.C. density at 20 °C: 15,52 kg/m³ (15,52 g/L)

Average carbon number: 8,95

Average molecular weight: 120,02 g/mol

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

# Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Not available

Not available

Not available

Not available

Not available

Non-applicable \*

Volatility:

Boiling point at atmospheric pressure: 123 °C
Vapour pressure at 20 °C: 2001 Pa

Vapour pressure at 50 °C: 10574,28 Pa (10,57 kPa)

Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# **IASEN**

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**

Non-applicable \*



# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Density at 20 °C: 1535,2 kg/m<sup>3</sup>

Relative density at 20 °C: 1,535

Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: Non-applicable \* Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \*

Decomposition temperature:

Melting point/freezing point:

Non-applicable \*

Non-applicable \*

Oxidising properties: Non-applicable \*

Flammability:

Explosive properties:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas):

Non-applicable \*

Autoignition temperature: 275 °C

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

**Explosive:** 

Lower explosive limit: Non-applicable \*
Upper explosive limit: Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

# 10.6 Hazardous decomposition products:

# IASEV<sup>®</sup>

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



# SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

# **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

    IARC: Quartz (RCS < 1 %) (1); Quartz (RCS > 10%) (1)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness
  - Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

# **IASEN**

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

# **Acriflex Mono**



# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

# Other information:

Non-applicable

# Specific toxicology information on the substances:

Identification	Acut	Genus	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one $(3:1)$	LD50 oral	100 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	300 mg/kg	Rat
EC: Non-applicable	LC50 inhalation	Non-applicable	

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-82-1	EC50	1 - 10 mg/L		Crustacean
EC: 919-446-0	EC50	1 - 10 mg/L		Algae
Ethanediol	LC50	53000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 107-21-1	EC50	51000 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-473-3	EC50	24000 mg/L (168 h)	Selenastrum capricornutum	Algae
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	0.1 - 1 mg/L		Crustacean
EC: Non-applicable	EC50	0.1 - 1 mg/L		Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Ethanediol	BOD5	0.47 g O2/g	Concentration	100 mg/L
CAS: 107-21-1	COD	1.29 g O2/g	Period	14 days
EC: 203-473-3	BOD5/COD	0.36	% Biodegradable	90 %

# 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Ethanediol	BCF	10	
CAS: 107-21-1	Pow Log	-1.36	
EC: 203-473-3	Potential	Low	

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Ethanediol	Koc	0	Henry	1,327E-1 Pa·m³/mol
CAS: 107-21-1	Conclusion	Very High	Dry soil	No
EC: 203-473-3	Surface tension	4,989E-2 N/m (25 °C)	Moist soil	No

# 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

# 12.6 Other adverse effects:

Not described

# **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous	

# IASEN SERVING FUTURE

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



### SECTION 13: DISPOSAL CONSIDERATIONS (continued)

# Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# **SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport (ADR/RID,IMDG,IATA)

# **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains (ethylenedioxy)dimethanol, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

### Seveso III:

Non-applicable

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

# 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### **SECTION 16: OTHER INFORMATION**

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

# IASEN<sup>®</sup>

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### **Acriflex Mono**



### SECTION 16: OTHER INFORMATION (continued)

# Texts of the legislative phrases mentioned in section 2:

H373: May cause damage to organs through prolonged or repeated exposure

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled

Acute Tox. 3: H301 - Toxic if swallowed Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Dam. 1: H318 - Causes serious eye damage Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage Skin Sens. 1A: H317 - May cause an allergic skin reaction

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 3: H336 - May cause drowsiness or dizziness

### Classification procedure:

STOT RE 2: Calculation method

### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

# Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.