SEEN BUILDING FUTURE

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Grip primer

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Surface Primer

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Diasen S.r.I.

Zona Ind.le Berbentina, 5

60041 Sassoferrato (AN) - Marche - Italia

Phone.: +39 0732 9718 - Fax: +39 0732 971899

diasen@diasen.com https://www.diasen.com

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Skin Sens. 1A: H317 - May cause an allergic skin reaction

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P272: Contaminated work clothing should not be allowed out of the workplace P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P333+P313: If skin irritation or rash occurs: Get medical advice/attention

P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Substances that contribute to the classification

2-methylisothiazol-3(2H)-one

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Acrylic resin

Components:

Date of compilation: 30/05/2019 Version: 1 Page 1/10



Grip primer



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration	
CAS:	2634-33-5	1,2-benzisothiazol-3	1,2-benzisothiazol-3(2H)-one □¹□ ATP CLP00		
EC: Index: REACH:	220-120-9 613-088-00-6 01-2120761540-60- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	<1 %	
CAS:	1319-77-3	Mix-cresol□ ² □	ATP CLP00		
EC: Index: REACH:	215-293-2 604-004-00-9 01-2119565142-45- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311; Skin Corr. 1B: H314 - Danger	<1 %	
CAS:	2682-20-4	2-methylisothiazol-3	(2H)-one □¹□ ATP ATP1		
EC: Index: REACH:	220-239-6 613-326-00-9 01-2120764690-50- XXXX	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger	<1 %	
CAS: EC:	55965-84-9 Non-applicable	reaction mass of 5-c one (3:1) \Box ¹ \Box	hloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- ATP ATP1		
Index: REACH:	613-167-00-5 Non-applicable	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<1 %	

 $[\]square^{1}\square$ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

[□]²□ Substance with a Union workplace exposure limit

IASEN[®]

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



Grip primer



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits			
Mix-cresol	IOELV (8h)	5 ppm	22 mg/m ³	
CAS: 1319-77-3 EC: 215-293-2	IOELV (STEL)			

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Mix-cresol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1319-77-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-293-2	Inhalation	Non-applicable	0,9 mg/m ³	3,5 mg/m ³	0,9 mg/m ³

DNEL (General population):

Non-applicable

PNEC:

Identification				
Mix-cresol	STP	1,14 mg/L	Fresh water	0,1 mg/L
CAS: 1319-77-3	Soil	0,05732 mg/kg	Marine water	0,003 mg/L
EC: 215-293-2	Intermittent	0,044 mg/L	Sediment (Fresh water)	0,32783 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00983 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

[&]quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATI	EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Grip primer



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	⊣ (DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0,02 % weight Non-applicable V.O.C. density at 20 °C:

Average carbon number: 5,27

115,44 g/mol Average molecular weight:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid Appearance: Viscous Colour: Yellowish Odour: Characteristic Odour threshold: Non-applicable *

Volatility:

105 °C Boiling point at atmospheric pressure: 2335 Pa Vapour pressure at 20 °C:

Vapour pressure at 50 °C: 12300,58 Pa (12,3 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: Non-applicable * Relative density at 20 °C: Non-applicable * Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: >20,5 cSt Concentration: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 30/05/2019 Version: 1 Page 5/10

IASEV[®]

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

pH: ~8,5 - 9,5

Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C: Non-applicable *

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 393 °C

Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Explosive:

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable Not applicable		Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Date of compilation: 30/05/2019 Version: 1 Page 6/10

IASEV[®]

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

 IARC: Quartz (RCS < 1 %) (1); Quartz (RCS > 10%) (1); Talc (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acut	Genus	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
EC: 220-120-9	LC50 inhalation	Non-applicable	
Mix-cresol	LD50 oral	240 mg/kg	Rat
CAS: 1319-77-3	LD50 dermal	300 mg/kg	Rat
EC: 215-293-2	LC50 inhalation	Non-applicable	



Grip primer



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification		te toxicity	Genus
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	100 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	300 mg/kg	Rat
EC: Non-applicable	LC50 inhalation	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
1,2-benzisothiazol-3(2H)-one	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 2634-33-5	EC50	0.1 - 1 mg/L		Crustacean
EC: 220-120-9	EC50	0.1 - 1 mg/L		Algae
Mix-cresol	LC50	12.8 mg/L (96 h)	Pimephales promelas	Fish
CAS: 1319-77-3	EC50	Non-applicable		
EC: 215-293-2	EC50	Non-applicable		
2-methylisothiazol-3(2H)-one	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 2682-20-4	EC50	0.1 - 1 mg/L		Crustacean
EC: 220-239-6	EC50	0.1 - 1 mg/L		Algae
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	0.1 - 1 mg/L		Crustacean
EC: Non-applicable	EC50	0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	Deg	radability	Biodegradability	
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %
Mix-cresol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 1319-77-3	COD	Non-applicable	Period	14 days
EC: 215-293-2	BOD5/COD	Non-applicable	% Biodegradable	49,7 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
1,2-benzisothiazol-3(2H)-one	BCF	2
CAS: 2634-33-5	Pow Log	1.45
EC: 220-120-9	Potential	Low
Mix-cresol	BCF	1
CAS: 1319-77-3	Pow Log	1.94
EC: 215-293-2	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Mix-cresol	Koc	11	Henry	Non-applicable
CAS: 1319-77-3	Conclusion	Very High	Dry soil	Non-applicable
EC: 215-293-2	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

Date of compilation: 30/05/2019 Version: 1 Page 8/10

ASEN[®] GREEN BUILDING FUTURE

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
	It is not possible to assign a specific code, as it depends on the intended use by the user	Non dangerous	

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), (ethylenedioxy)dimethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 10, 11, 12, 13); 2-methylisothiazol-3(2H)-one (Product-type 6, 11, 12, 13); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

ASEN® GREEN BUILDING FUTURE

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

Grip primer



SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled

Acute Tox. 2: H330 - Fatal if inhaled Acute Tox. 3: H301 - Toxic if swallowed

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin

Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage Skin Corr. 1C: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction Skin Sens. 1A: H317 - May cause an allergic skin reaction

Classification procedure:

Skin Sens. 1A: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.