

Aquabond

Single-component, water-based adhesion primer (such as **Aquabond**), ideal for creating a good adhesion bridge on cementitious or lime-based plasters, smoothing compounds, painted plasters, tile adhesives, paints and other types of acrylic coatings. It creates a film which, when dry, is characterised by good adhesion even on very smooth and impermeable mineral substrates. Minimum required characteristics: Adhesion on cementitious supports > 4,0 N/mm² | 580.15 lb/in² (excellent); Adhesion on wood > 4,0 N/mm² | 580.15 lb/in² (excellent); Adhesion on metal > 4,0 N/mm² | 580.15 lb/in² (excellent); Adhesion on glass > 4,0 N/mm² | 580.15 lb/in² (excellent); Adhesion of the system *Aquabond* + *Diathonite Evolution* on cork panel 85,5 N (good); Water vapour permeability coefficient $\mu = 788$.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com
PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

