

Decorkrete

Decorative micro-cement coating (such as **Decorkrete**), for indoor and outdoor floors and walls. Ideal as a finish and as a skimming coat, formulated with a base of special powdered resins and innovative additives that make it highly workable and provide an excellent aesthetic effect. Characterised by good weather resistance and excellent filling power, it can be used both indoors and outdoors. It produces perfectly smooth, crack-free skim coats and coatings with a modern appearance. The ease of processing allows for individual surface effects. Minimum required characteristics: Compressive strength_(after 28 days) 24.59 N/mm² | 3599.48 lbf/in² (C20); Tensile strength_(after 28 days) 6.35 N/mm² | 920.99 lbf/in² (F6); Adhesion of *Aquafloor Eco gloss* on *Decorkrete* 1.00 MPa=N/mm² | 145.04 lbf/in²; Adhesion of *Aquafloor Eco matte* on *Decorkrete* 1.13 MPa=N/mm² | 163.89 lbf/in².

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com

PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

